

## 1. Applications

EUROFLEX® Edge and Corner Profile are used as edging for playgrounds and playing surfaces of all types over hard, level substructures.

Their beveled edges facilitate access with wheelchairs and reduce the danger of stumbling at the edge of the surface.

EUROFLEX® Edge and Corner Profile are manufactured by an environmentally-friendly process and can be recycled as process raw material at the end of their service life.

## 2. Material

Rubber granulate: granulated recycled rubber

Binding agent: MDI polyurethane

## 3. Characteristics

Colour: red, green, grey or black (minor colour variations possible.)

Surface: smooth with open pores, beveled edges

## 4. Dimensions / Tolerances

L x W x T, Weights:

Edge Profile:	1000 x 250 x 30/10 mm approx. 4,0 kg
	1000 x 250 x 40/10 mm approx. 6,2 kg
	1000 x 250 x 50/20 mm approx. 7,8 kg
	1000 x 250 x 70/20 mm approx. 8,5 kg
	1000 x 250 x 80/20 mm approx. 10,5 kg
	1000 x 250 x 110/20 mm approx. 13,0 kg
Corner Profile:	1000 x 250 x 30/10 mm approx. 3,2 kg
	1000 x 250 x 40/10 mm approx. 6,5 kg
	1000 x 250 x 50/20 mm approx. 8,0 kg
	1000 x 250 x 70/20 mm approx. 8,7 kg
	1000 x 250 x 80/20 mm approx. 9,0 kg
	1000 x 250 x 110/20 mm approx. 12,5 kg
Dimensional tolerances:	+/- 0,8 %

## 5. Test Data

Permissible fall height: in accordance with DIN EN 1176.1:2008, EN 1176.1:2008  
Chemical resistance: conditionally resistant to acids and bases  
Cold fracture resistance: 24h / -40°C, no fracture  
Cold crack resistance: 5h / -30°C, no cracks  
Production facility inspection

## 6. Installation

Clean the existing paved substructure and be certain it is dry and level.  
Securely cement EUROFLEX® Edge and Corner Profile onto the substructure using dabs of 1-  
component PU adhesive cement.  
Cement the joints between the slabs together with adhesive cement.